

TECHNICAL DATA SHEET

	Reference:		POTCART1300FRC					
	Name :		POJ. SAŁ.PAP.1300ML FAT RESIST POKEPACK CARTON					
	Family :							
	Box Barcode : Customs Code :		5903424938551 48236990					
		CHARACTE	RISTICS	OF PROD	ИСТ			
		Lengt	h	Width	1	Height	Diameter	
External Dimensions :	(mm)		-		-	68	183	
Internal Dimensions :	(mm)	-			-	-	-	
Comments						I		
Capacity :		1300		(ml)				
Net weight :		23,15		(gr)		(+/- 5 %)		
Material :		PAPIER/	CARTON			, , , , , , , , , , , , , , , , , , ,		
Color :		ECRU						
Temperature Range :		+5/+70	(°C)					
Anti-Mist Treatment :		-	(-)					
		CHARACTE	RISTICS	OF SLEE	VE			
Sleeve Barcode :		5901360	015640					
Sleeve units :		50						
		CHARAC	TERISTIC	S OF BO	X			
Units of product :		300						
Dimensions of Box :		563 x 38	3 x 526		(mm)	(+/- 10mm)		
Volume of Box :		0,11		(m3)		(+/- 10%)		
Gross Weight of Box :		7,656		(kg)		(+/- 10%)		
		CHARACTE						
	-	Type of pallet	: Euro - 8	00 X 120	0 mm			
Boxes per layer :		4						
Layers per pallet :		4						
Boxes per pallet :		16						
Products of pallet :		4 800		(1.0)		(+/- 10%)		
Pallet gross weight : Pallet height :		142		(kg) (m)		(+/- 10%) (+/- 10%)		
		2,254		(m)		(1/- 10/0)		

STORAGE AND TRANSPORT CONDITIONS

- in a dry and clean storage, on the pallets, wrapped with the stretch film protecting from dust, dirt, mechanical contamination and humidity.

In a distance of at least 1m from the active heating source.
 Away from direct sunlight.

- Do not stack the pallets.

We recommend storage at temperatures between (-10) and (+50) degrees Celsius
 In case of non-fulfillment of the condition of the temperature in the warehouse, it is recommended to seasoning the containers

in corrugated boxes, not wrapped with a stretch film at ambient temperature of production conditions for 24 hours before use. - Storage period: not determined - we recommend 24 months.

Do not stack the pallets.
To be carried with covered transport.